

a distal cutting element disposed on said distal tip; and

C²
a fixation element which has a free end and which is disposed on said distal end proximal of said distal tip, and which is configured for securing the distal end of said medical device within target tissue at said desired location.

p 56. (Amended) A method of performing a medical procedure, comprising:

- a) providing a medical device comprising a shaft having a distal end with a tip, a proximal end, a fixation element which has a free end and which is spaced proximal to the distal tip, a distal cutting element disposed on said distal tip,
- b) placing the distal end of the shaft in body tissue within a patient's body, so that the distal end is disposed within target tissue; and
- c) extending into the target tissue the free end of the fixation element from a side of the shaft spaced proximal to the distal tip, so that the free end engages target tissue and the distal end of the shaft becomes secured within the target tissue.

C³ 9 56. (Amended) A method of performing a medical procedure, comprising:

- a) providing a medical device comprising a shaft having a distal end with a distal tip, a distal cutting element disposed on said distal tip, a proximal end, a fixation element which has a free end and which is spaced proximal to the distal tip,
- b) cutting through tissue of a patient's body with said distal cutting element;
- c) placing the distal end of the shaft in body tissue within a patient's body, so that the distal end is disposed adjacent target tissue; and
- d) radially extending into the target tissue a fixation element from a side of the shaft spaced proximal to the distal end, said member having a free end configured for engaging tissue, so that the distal end of the shaft becomes secured adjacent the target tissue.
-

27

C

116
68. (Amended) A method for acquiring a tissue specimen from target tissue, comprising:

- 116
- a) providing a tissue acquisition device having a shaft with a distal end with a distal tip, a proximal end, a distal cutting element disposed on said distal tip, a fixation element spaced proximally from the distal tip and having a free end,
 - b) placing the distal end of the shaft in target tissue within a patient's body, so that the distal tip is disposed distally adjacent the target tissue;
 - c) securing the distal end of the shaft within the target tissue by extending into the target tissue the free end of the fixation element; and
 - d) acquiring a tissue specimen of target tissue.

Please add the following new claims:

119
69. A medical device for localization of target tissue comprising:

a shaft having a distal end with a distal tip, and being configured for placement of said distal end into a patient's body tissue at a desired location within target tissue;

119
a radially expandable side-cutting element which has an expanded configuration for cutting a tissue sample from target tissue and which is disposed on said shaft proximal of said distal tip; and

119
a fixation element which has a free end, which is disposed on said distal end of the shaft proximal of said distal tip and which is configured for securing the distal end of said medical device within target tissue at said desired location.

119
69. The medical device of claim 68, wherein said radially expandable side-cutting element is an electrosurgical cutting element.

21
70. The medical device of claim 68, wherein said fixation element is configured for penetrating target tissue.

22
71. The medical device of claim 68, wherein said fixation element comprises at least one radially extendable and retractable member.

23
72. The medical device of claim 71, wherein said fixation element comprises a plurality of radially extendable and retractable members which have free ends configured for securing the distal end of the shaft within target tissue.

24
73. A method of performing a medical procedure, comprising:

a) providing a medical device comprising a shaft having a distal end with a distal tip, a fixation element which has a free end and which is disposed proximal to the distal tip, and a radially expandable side-cutting element configured for cutting a tissue sample and disposed on said shaft proximal of said distal tip;

b) advancing the distal end of the shaft within a patient's body, so that the distal end is disposed within target tissue; and

c) extending into the target tissue the free end of the fixation element so that the distal end of the shaft becomes secured within the target tissue.

25
74. The method of claim 73, wherein said fixation element comprises at least one radially extendable and retractable member.

26
75. The method of claim 73, wherein said fixation element comprises a plurality of radially extendable and retractable members.

27
76. A method for acquiring a specimen of target tissue, comprising:

a) providing a tissue acquisition device comprising a shaft having a distal end with a distal tip, a fixation element which has a free end and which is spaced proximal to the distal tip, and a radially expandable side-cutting element configured for cutting a tissue specimen and disposed on said shaft proximal of said distal tip;

b) advancing the distal end of the shaft in body tissue within a patient's body, so that the distal end is disposed within the target tissue;

c) ~~b)~~ securing the distal end of the shaft within the target tissue by extending into the target tissue the free end of the fixation element configured for engaging tissue; and

d) ~~c)~~ cutting tissue with said radially expandable side-cutting element effective to separate one or more tissue specimens of target tissue.

28/ 28
77. The method of claim 76, wherein the step of securing the distal end of the shaft comprises extending at least one radially extendable and retractable member from a side of the shaft spaced proximal to the distal end.

29/ 28
78. The method of claim 77, wherein the step of securing the distal end of the shaft comprises extending a plurality of radially extendable and retractable members from a side of the shaft spaced proximal to the distal end.

30

79. A medical device for localization of target tissue comprising:

a shaft having a distal end with a distal tip, and being configured for placement of said distal end into a patient's body at a desired location;

a distal cutting element disposed on said distal tip;

a radially expandable side-cutting element configured for cutting a tissue sample from target tissue and disposed on said shaft proximal of said distal tip; and

a fixation element which has a free end, which is disposed on said distal end proximal of said distal tip and which is configured for securing the distal end of said medical device within target tissue at said desired location.

31
80. The medical device of claim 79, wherein said radially expandable side-cutting element is an electrosurgical cutting element.

32
81. The medical device of claim 79, wherein said distal cutting element is an electrosurgical cutting element.

33
82. The medical device of claim 79, wherein said fixation element is configured for penetrating tissue.

34
83. The medical device of claim 79, wherein said fixation element comprises at least one radially extendable and retractable member.

35
84. The medical device of claim 83, wherein said fixation element comprises a plurality of radially extendable and retractable members which are radially extendable and retractable from a side of the distal end of the shaft, said members having free ends and being configured for securing the distal end of the shaft adjacent target tissue.

36
85. A method of performing a medical procedure, comprising:
a) providing a medical device comprising a shaft having a distal end with a distal tip, a distal cutting element on the distal tip, a radially expandable side-cutting

31

C

element configured for cutting a tissue sample and disposed on said shaft proximal of said distal tip, and a fixation element which has a free end, which is spaced proximal to the distal tip and which is configured for engaging tissue,

b) advancing the medical device within a patient's body while cutting through tissue with said distal cutting element until the distal end of the shaft is disposed within target tissue; and

c) extending into the target tissue the free end of the fixation element so that the distal end of the shaft becomes secured within the target tissue.

37
86. The method of claim 85, wherein said fixation element comprises at least one radially extendable and retractable member.

38
87. The method of claim 86, wherein said fixation element comprises a plurality of radially extendable and retractable members.

39
88. The method of claim 86, wherein said distal cutting element is an electrosurgical cutting element.

40
89. The method of claim 86, wherein said cutting step comprises cutting target tissue.

41
90. The method of claim 86, wherein said cutting step comprises cutting through target tissue.

42
91. The method of claim 90, wherein said placing step comprises placing the distal end of the shaft in a patient's body so that the distal tip of the distal end is disposed adjacent and distal to target tissue.